

TECHNICAL DATA SHEET

REVISED: 16/12/2022

VICEVERSA EASY PROTECT

PROFESSIONAL LINE FOR WALL COVERINGS



Mono-component protector developed for use with all types of wallcoverings. It allows the wallcovering to be washed, and provides a superior scratch resistance. It is suitable for both domestic and trade use.

Suitable for:

- Wallpapers
- Glass fibre wallcovering
- Non-woven wallcovering
- Textured vinyl wallcovering
- Vinyl or digitally printed non-woven wallcovering

TECHNICAL FEATURES:

- + Opaque
- + Pleasant aesthetic finish
- + Does not affect the colour of the wallcovering
- + Does not leave marks
- + Does not yellow
- + Solvent free

The EASY PROTECT formula contains our exclusive sanitising gel with a Thymol base, THYMOLGEL. Thymol, antibacterial and anti-viral, is a phenol derived from the Thyme plant. This unique addition is both sanitising and hygienic over a long time, and for all types of wallcoverings using EASY PROTECT.

PRODUCT PREPARATION

EASY PROTECT is a ready to use mono-component protector

SURFACE PREPARATION

All surfaces must be dry, absorbent, solid, free from dust, paints and oils. Any gaps should be filled with our ultra-light GLASTER filler. We also recommend using a sealing primer to bind and clean the wall. PRIMER AC is ideal for binding and for cleaning, whereas PRIMER SP is specifically developed to protect and to prevent walls from mould and bacteria where the environment may be humid. To be assured of a complete sanitisation and anti-bacterial protection we recommend using our PRIMER+ PLUS with THYMOLGEL.

APPLICATION

EASY PROTECT is a ready to use mono-component protector, mix before use to eliminate any sedimentation. Apply the product directly to the wallcovering with a sponge roller, making one or two coats. Wait at least 1 hour between coats for the surface to become completely dry. Do not use in areas in direct contact with water.

ENVIRONMENTAL INSTALLATION CONDITIONS

Ambient temperature and of the surface: min +10°C - max. +30°C. Relative air humidity: max. 75%. Also ensure the site has effective air circulation to avoid a build-up of humidity in the environment, which could cause hardening problems particularly in close quarters.

www.acm-italy.com

TECHNICAL DATA SHEET

REVISED: 16/12/2022

VICEVERSA EASY PROTECT

PROFESSIONAL LINE FOR WALL COVERINGS



COVERAGE

For glass fibre and for textured vinyl: approx 7-8 m²

For non-woven, paper and vinyl: 11-12 m²

CLEANING

Clean the equipment with fresh water immediately after use, or remove mechanically.

CONTRA-INDICATIONS

Do not use this product on a non-absorbent surface, do not apply to damp or moldy walls, or where the surface has not been prepared adequately. Any excess paste on the surface must be wiped off immediately using a damp cloth.

PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
40148-1	1	kg	Plastic Bottle	12

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 12 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

PRODUCT TECHNICAL DATA

Colour	White (dries clear)
Physical Appearance	Liquid
PH	7.9
Viscosity	500-700 cps
Percentage of solids	Approx 30%
Operating Temperatures	Between -10°C +50°C
Minimum Installation Temperature	+5°C
Touch Dry	30 minutes at 20°C
Completely Dry	48 hours

FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

DISCLAIMER

The information contained in the data sheet, based on results of our long experience, are for information only. Therefore, those who intend to use it are required to assess whether the product is suitable for their use, and to assume responsibility for its use.