



Easipaste® Ready Mixed Wallcovering Adhesive **Product Information Sheet**

Description

Easipaste® is a technically advanced wallpaper adhesive suitable for all types of wallcoverings including vinyl, blown vinyl, heavy embossed, washables and 'paste the wall' wallcoverings. No mixing or dilution is required. The super smooth easy spread adhesive has strong grab and easy slide properties for perfect wallpaper hanging.

Coverage

1kg of Easipaste® is sufficient to hang approximately one 10 metre roll of standard wallcovering, or half a roll of embossed or heavy embossed wallcovering.

Directions

Preparation:

Surfaces should be sound, dry, clean and free from damp, dust and grease. Gloss painted surfaces should be sanded to provide a key. Very porous surfaces such as new plaster should be sealed with PVA or Size.

Application:

Always follow the wallcovering manufacturer's instructions. For traditional wallcoverings apply Easipaste® by brush or roller to the reverse of the wallcovering ensuring complete and even coverage. Avoid getting the adhesive on the patterned side of the paper. For heavy coverings allow time for the paste to soak until supple. Immediately remove any paste that comes into contact with patterned sides of the wallcovering.

For 'paste the wall' wallcoverings apply Easipaste® evenly and generously onto the wall surface, ensuring that the pasted area is slightly wider than the width of the wallpaper.

Cleaning & Storage

Any accidental splashes should be removed immediately with a clean, damp cloth or sponge. Tools and equipment should be cleaned with water immediately after use. Protect from frost.

Health and Safety

See MSDS for full information.

Contains biocidal in-can preservatives: 2-methyl-2H-isothiazol-3-one & 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Keep away from children and animals. If adhesive comes into contact with skin, wash with warm water. If skin irritation or rash occurs: Get medical advice/attention.

Technical Data

Measurement	Value	Test Method
Physical State	Paste	Visual
Colour	Off White	Visual
Odour	PVA Type	
Flash point	Not Applicable	
VOC content	None	
Viscosity	200 – 300 cps	Spindle 6/ speed 10 @ 25°C
pH	6.0 – 7.0	

Packing Specification

<u>Pack Size</u>	<u>Product Code</u>	<u>Pack Barcode</u>	<u>Carton Barcode</u>	<u>Packs Per Carton</u>	<u>Cartons Per Pallet</u>	<u>Packs Per Pallet</u>	<u>Ti</u>	<u>Hi</u>
1Kg tub	58510973	5010789510978	05010789513078	6	70	420	10	7
2.5Kg Bucket	58510920	5010789510923	-----	N/A	N/A	168	28	6
5Kg Bucket	58510930	5010789510930	-----	N/A	N/A	100	25	4
10Kg Bucket	58510940	5010789510947	-----	N/A	N/A	60	12	5

Customs Tariff Code

3506 9900

Shipping Classification

Non-Hazardous for shipping purposes